GF1AS~GF1MS

GPP SURFACE MOUNT RECTIFIER

VOLTAGE 50 to 1000 Volts **CURRENT** 1.0 Amperes

FEATURES

- For surface mounted applications
- Low profile package
- Ideal for automated placement
- High temperature soldering : 260°C /10 seconds at terminals
- Glass Passivated Chip Junction
- In compliance with EU RoHS 2002/95/EC directives

SOD-123FL



Dimensions in millimeters

MECHANICAL DATA

Case:SOD-123S,Molded Plastic over passivated junction

- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 0.01 gram

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

PARAMETER	SYMBOL	GF1AS	GF1BS	GF1DS	GF1GS	GF1JS	GF1KS	GF1MS	UNITS
Marking Code		A1	A2	A3	A4	A5	A6	A7	
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward Current (Note 1)	$I_{F(AV)}$	1.0							A
Peak one cycle surge forward current (non-repetitive)	I_{FSM}	30 (60Hz)							A
Maximum Forward Voltage at 1.0A	V_F	1.1							V
Maximum DC Reverse Current at TA=25°C Rated DC Blocking Voltage TA=125°C	I_R	10 50							uA
Typical Junction capacitance at 4V, MHz	C_J	4							pF

ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

PARAMETER	SYMBOL	GF1AS	GF1BS	GF1DS	GF1GS	GF1JS	GF1KS	GF1MS	UNITS
Typical thermal resistance (Note 2)	$R_{\theta JA}$	65							°C / W
Operating and Storage Temperature Range	T_J, T_{STG}	-50 TO +150							°C

NOTES:

1.Pulse test: 300u pulse width, 1% duty cycle.

2.Soldering land: 6mm x 6mm

http://www.luguang.cn mail:lge@luguang.cn



Fig.1 FORWARD CURRENT DERATING CURVE



Fig.2-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS



Fig.3 TYPICAL REVERSE CHARACTERISTICS



Fig.4 TYPICAL JUNCTION CAPACITANCE