Gunter Semiconductor GmbH

GFC150

N Channel Power MOSFET with extremely low $R_{DS(ON)}$



Chip Specification

General Description:

* Advanced Process Technology
* Dynamic dV/dt Rating
* **175℃ Operating Temperature**
* **Fast Switching**
* **Fully Avalanche Rated**
* ***Extremely low $R_{DS(ON)}$***



Mechanical Data:

D27	
Dimension	**6.53mm x6.53mm**
Thickness:	**400 μm**
Metallization**:**	
Top : :	**Al**
Backside :	**CrNiAg / Au**
Suggested Bonding Conditions:	
Die Mounting:	**Solder Perform**
95/5 PbSn or 92.5./2.5/5 PbAgIn	
Source Bonding Wire**:**	**20 mil Al**

Absolute Maximum Rating @Ta=25℃

Characteristics	Symbol	Limit	Unit	Test Conditions
Drain-to-Source Breakdown Voltage	V(BR)DSS	100	V	VGS=0V, ID=250μA
Static Drain-to - Source On-resistance	RDS(ON)	0.055	Ω	VGS=10V, ID=25A
Continuous Drain current (in target package)	ID@25℃	41	A	VGS=10V
Continuous Drain current (in target package)	ID@100℃	29	A	VGS=10V
Operation Junction	Tj	-55~175	℃	
Storage Temperature	TSTR	-55~175	℃	

Target Device: IRFP150

TO-247AC	PD	230	W	@Tc=25℃