BGA Heat Sink (High Aspect Ratio Ext.) **Straight Fin**





ATS Part#:

Description:

ATS019019016-SF-60

19.00 x 19.00 x 16.00 mm BGA Heat Sink (High Aspect Ratio Ext.) Straight Fin

Heat Sink Type: Straight Fin Heat Sink Attachment: Equivalent Part Number: N/A

superGRIP

*Image above is for illustration purpose only.

Features & Benefits

- · High aspect ratio, straight fin heat sinks that are ideal for compact PCB environments
- Features a low profile, slant fin array that offers many of the performance benefits of maxiFLOW™ at a great value .
- . Higher performance helps ensure reliable product life at a lower cost than other extruded heat sinks
- Comes standard without interface material or with most common pressure sensitive thermal tapes as a custom option ٠

Thermal Performance

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	8.19 °C/W	6 °C/W	5.1 °C/W	4.5 °C/W	4.1 °C/W	3.8 °C/W	3.6 °C/W
	Ducted Flow	4.7	4	3.5	3.2	3	2.8	2.7

Product Detail

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	тім	Finish
(Marco)	19.00 mm	19.00 mm	16.00 mm	19 mm	N/A	BLACK-ANODIZED
Image above is for illustration purpose only.	 Dimension Dimension Thermal papplication ATS resension ATS certifier 	n D is fin tip to fin tip performance data are n. rves the right to upd nce.	e provided for refere ate or change its pro	m of the base to the nce only. Actual perf iducts without notice G-6 and REACH com ble.	formanc to impr	e may vary by

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



© 2013 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA