

### Small Signal Diode




#### Features

- ◇ Fast switching speed
- ◇ Surface device type mounting
- ◇ Moisture sensitivity level 1
- ◇ Matte Tin(Sn) lead finish with Nickel(Ni) underplate
- ◇ Pb free version and RoHS compliant
- ◇ Green compound (Halogen free) with suffix "G" on packing code and prefix "G" on date code


#### Mechanical Data

- ◇ Case :SOT-23 small outline plastic package
- ◇ Terminal: Matte tin plated, lead free., solderable per MIL-STD-202, Method 208 guaranteed
- ◇ High temperature soldering guaranteed: 260°C/10s
- ◇ Weight : 0.008gram (approximately)
- ◇ Marking Code : KL1, KL2, KL3, KL4


#### Pin Configuration




**BAT54**



**BAT54A**



**BAT54C**



**BAT54S**

#### Ordering Information

| Package | Part No.   | Packing      | Marking |
|---------|------------|--------------|---------|
| SOT-23  | BAT54 RF   | 3K / 7" Reel | KL1     |
| SOT-23  | BAT54A RF  | 3K / 7" Reel | KL2     |
| SOT-23  | BAT54C RF  | 3K / 7" Reel | KL3     |
| SOT-23  | BAT54S RF  | 3K / 7" Reel | KL4     |
| SOT-23  | BAT54 RFG  | 3K / 7" Reel | KL1     |
| SOT-23  | BAT54A RFG | 3K / 7" Reel | KL2     |
| SOT-23  | BAT54C RFG | 3K / 7" Reel | KL3     |
| SOT-23  | BAT54S RFG | 3K / 7" Reel | KL4     |


#### Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.

#### Maximum Ratings


| Type Number                                 | Symbol          | Value      | Units |
|---|-----------------|------------|-------|
| Peak Repetitive Peak reverse voltage        | $V_{RRM}$       | 30         | V     |
| Working Peak Reverse Voltage                | $V_{RWM}$       |            |       |
| DC Reverse Voltage                          | $V_R$           |            |       |
| Forward Continuous Current                  | $I_F$           | 200        | mA    |
| Repetitive Peak Forward Current             | $I_{FRM}$       | 200        | mA    |
| Forward surge current @t<1.0s               | $I_{FSM}$       | 600        | mA    |
| Power Dissipation                           | $P_d$           | 200        | mW    |
| Thermal resistance, junction to ambient air | $R_{\theta JA}$ | 500        | °C/W  |
| Operating and Storage temperature           | $T_j, T_{STG}$  | -55 to 150 | °C    |

#### SOT-23



| Dimensions | Unit (mm) |      | Unit (inch) |       |
|------------|-----------|------|-------------|-------|
|            | Min       | Max  | Min         | Max   |
| A          | 2.80      | 3.00 | 0.110       | 0.118 |
| B          | 1.20      | 1.40 | 0.047       | 0.055 |
| C          | 0.30      | 0.50 | 0.012       | 0.020 |
| D          | 1.80      | 2.00 | 0.071       | 0.079 |
| E          | 2.25      | 2.55 | 0.089       | 0.100 |
| F          | 0.90      | 1.20 | 0.035       | 0.043 |
| G          | 0.550 REF |      | 0.022 REF   |       |

#### Suggested PAD Layout




**Small Signal Diode**


**Electrical Characteristics**

| Type Number               |   | Symbol     | Min | Max  | Units   |
|---------------------------|---|------------|-----|------|---------|
| Reverse Breakdown Voltage | $I_R = 100\mu A$                                  | $V_{(BR)}$ | 30  | --   | V       |
| Forward Voltage           | $I_F = 0.1mA$                                     | $V_F$      | --  | 0.24 | V       |
|                           | $I_F = 1mA$                                       |            | --  | 0.32 | V       |
|                           | $I_F = 10mA$                                      |            | --  | 0.40 | V       |
|                           | $I_F = 30mA$                                      |            | --  | 0.50 | V       |
|                           | $I_F = 100mA$                                     |            | --  | 1.00 | V       |
| Reverse current           | $V_R = 25V$                                       | $I_R$      | --  | 2.0  | $\mu A$ |
| Total Capacitance         | $V_R = 1V, f = 1.0MHz$                            | $C_T$      | --  | 10   | pF      |
| Reverse Recovery Time     | $I_F = I_R = 10mA, R_L = 100\Omega, I_{RR} = 1mA$ | $t_{rr}$   | --  | 5.0  | nS      |

**Tape & Reel specification**




| Item                   | Symbol | Dimension(mm) |
|------------------------|--------|---------------|
| Carrier width          | A      | 3.15 ± 0.10   |
| Carrier length         | B      | 2.77 ± 0.10   |
| Carrier depth          | C      | 1.22 ± 0.10   |
| Sprocket hole          | d      | 1.50 ± 0.10   |
| Reel outside diameter  | D      | 178 ± 1       |
| Reel inner diameter    | D1     | 55 Min        |
| Feed hole width        | D2     | 13.0 ± 0.20   |
| Sprocket hole position | E      | 1.75 ± 0.10   |
| Punch hole position    | F      | 3.50 ± 0.05   |
| Sprocket hole pitch    | P0     | 4.00 ± 0.10   |
| Embossment center      | P1     | 2.00 ± 0.05   |
| Overall tape thickness | T      | 0.229 ± 0.013 |
| Tape width             | W      | 8.10 ± 0.20   |
| Reel width             | W1     | 12.30 ± 0.20  |




**Small Signal Diode**

**Rating and Characteristic Curves**


**FIG 1 Typical Forward Characteristics**



**FIG 2 Typical Reverse Characteristics**



**FIG 3 Admissible Power Dissipation Curve**



**FIG 4 Typical Junction Capacitance**

