

Part Number: C1707

Revision Level: 11/19/2012

**4C 18AWG 16/30BC PP, PVC****COMMAND® SERIES****A. CONSTRUCTION**

Conductor: 18 AWG 16/30 BC  
Insulation: .009" Wall, Polypropylene (PP)  
Cable Core: 4C @ 4.00" LHL  
Jacket: .030" Polyvinyl Chloride (PVC)  
Print Legend:

**DIAMETERS**

.047" nom  
.066" nom  
.160" nom  
.220" nom

**CAROL® -- C1707 -- 4C 18AWG COMMAND SERIES AUDIO CABLE (UL) E60233-8  
CL3 60C -- CSA C/US CMG 80C OR CSA AWM I/II A/B 80C 600V  
FT4 -- ROHS -- MADE IN USA (Date code) (Seq Footage)**

**B. INDUSTRY APPROVALS**

National Electrical Code	Article 725
UL Standard 444	Type CL3
CSA International	Type AWM I/II A/B

**C. ELECTRICAL PROPERTIES**

Temperature: -20°C to +80°C  
Suggested Working Voltage: 600V Max  
Conductor DCR: 6.55 Ohms/M' @ 20°C (nom)  
Mutual Capacitance: 18.8 pF/ft @ 1kHz (nom)

**D. COLOR CODE**

Item	COLOR
1	BLACK
2	RED
3	WHITE
4	GREEN

**E. CUSTOMER APPROVAL**

Signature: \_\_\_\_\_  
Date: \_\_\_\_\_