




## MULTILAYER CERAMIC CHIP CAPACITORS



### CGJ Series Extended Life Capacitors

Type: CGJ2 [EIA CC0402]  
CGJ3 [EIA CC0603]  
CGJ4 [EIA CC0805]  
CGJ5 [EIA CC1206]

Issue date: December 2011

TDK MLCC  
US Catalog

Version B11

## REMINDERS


Please read before using this product

### SAFETY REMINDERS



### REMINDERS

1. If you intend to use a product listed in this catalog for a purpose that may cause loss of life or other damage, you must contact our company's sales window.
2. We may modify products or discontinue production of a product listed in this catalog without prior notification.
3. We provide "Delivery Specification" that explain precautions for the specifications and safety of each product listed in this catalog. We strongly recommend that you exchange these delivery specifications with customers that use one of these products.
4. If you plan to export a product listed in this catalog, keep in mind that it may be a restricted item according to the "Foreign Exchange and Foreign Trade Control Law". In such cases, it is necessary to acquire export permission in harmony with this law.
5. Any reproduction or transferring of the contents of this catalog is prohibited without prior permission from our company.
6. We are not responsible for problems that occur related to the intellectual property rights or other rights of our company or a third party when you use a product listed in this catalog. We do not grant license of these rights.
7. This catalog only applies to products purchased through our company or one of our company's official agencies. This catalog does not apply to products that are purchased through other third parties.



## CGJ Series Extended Life Capacitors

Type: CGJ2 (C1005), CGJ3 (C1608),  
CGJ4 (C2012), CGJ5 (C3216)

### Features




- Extended Life series capacitor featuring increased evaluation during manufacturing to promote longer life
- Life test performs at 2x rated voltage for 2000 hrs
- Reliability tests based on MIL-STD requirements
- Guaranteed TC Bias and Hot IR performance
- Anti-counterfeit/tamper-proof seal to assist in the identification of authentic TDK CGJ products. The condition of the seal also indicates if the product has been tampered with in the supply chain
- Certificate of Compliance (CofC) documentation is provided for each CGJ lot. Consumers of CGJ products can view each lot specific CofC on the TDK website
- Available optional UHF (Ultra High Frequency) RFID tag to allow integration with customer RFID programs such as inventory management
- CGJ customer priority backed by TDK factory support by 3/3/7 policy (3hrs: acknowledgement, 3 days: response with initial failure mode, 7 days: full failure analysis report)

### Applications



- Smart Meter
- Smart Grid
- Solar Inverters
- Charging station
- Applications that require extended life performance

### Shape & Dimension



Dimensions in mm



### Part Number Construction

**CGJ 5 L 2 X7R 1A 106 K T XXXX**

Series Name

Dimensions L x W (mm)

| Symbol | Length           | Width            |
|--------|------------------|------------------|
| 2      | 1.00 ± 0.05      | 0.50 ± 0.05      |
| 3      | 1.60 ± 0.10      | 0.80 ± 0.10      |
| 4      | 2.00 ± 0.20      | 1.25 ± 0.20      |
| 5      | 3.20 ± 0.20      | 1.60 ± 0.20      |
|        | 3.20 +0.30/-0.10 | 1.60 +0.30/-0.10 |

Thickness T (mm)

| Symbol | Thickness | Symbol | Thickness |
|--------|-----------|--------|-----------|
| B      | 0.50 mm   | H      | 1.15 mm   |
| C      | 0.60 mm   | J      | 1.25 mm   |
| E      | 0.80 mm   | L      | 1.60 mm   |
| F      | 0.85 mm   |        |           |

Voltage Condition for Life Test

| Symbol | Condition |
|--------|-----------|
| 2      | 2 × R.V.  |

Temperature Characteristic

| Temperature Characteristic | Capacitance Change | Temperature Range |
|----------------------------|--------------------|-------------------|
| C0G                        | 0±30 ppm/°C        | -55 to +125°C     |
| X7R                        | ± 15%              | -55 to +125°C     |

Internal Codes

Packaging Style

| Packaging Code | Style       |
|----------------|-------------|
| T              | Tape & Reel |

Capacitance Tolerance

| Tolerance Code | Tolerance |
|----------------|-----------|
| J              | ± 5%      |
| K              | ± 10%     |
| M              | ± 20%     |

Nominal Capacitance (pF)

The capacitance is expressed in three digit codes and in units of pico Farads (pF). The first and second digits identify the first and second significant figures of the capacitance. The third digit identifies the multiplier. R designates a decimal point.

| Capacitance Code | Capacitance       |
|------------------|-------------------|
| 0R5              | 0.5pF             |
| 010              | 1pF               |
| 102              | 1,000pF (1nF)     |
| 105              | 1,000,000pF (1µF) |

Rated Voltage (DC)

| Voltage Code | Voltage (DC) |
|--------------|--------------|
| 0J           | 6.3V         |
| 1A           | 10V          |
| 1C           | 16V          |
| 1E           | 25V          |
| 1H           | 50V          |



## Capacitance Range Chart

# CGJ2 [EIA CC0402]

### Capacitance Range Chart

Temperature Characteristics: C0G (0±30 ppm/°C)

Rated Voltage: 50V (1H)

| Capacitance (pF) | Cap Code | Tolerance | C0G      |
|------------------|----------|-----------|----------|
|                  |          |           | 1H (50V) |
| 100              | 101      | J: ± 5%   | █        |
| 120              | 121      |           | █        |
| 150              | 151      |           | █        |
| 180              | 181      |           | █        |
| 220              | 221      |           | █        |
| 270              | 271      |           | █        |
| 330              | 331      |           | █        |
| 390              | 391      |           | █        |
| 470              | 471      |           | █        |
| 560              | 561      |           | █        |
| 680              | 681      |           | █        |
| 820              | 821      |           | █        |
| 1000             | 102      |           | █        |

Standard Thickness 0.50 mm

### Capacitance Range Chart

Temperature Characteristics: X7R (± 15%)

Rated Voltage: 50V (1H), 25V (1E), 16V (1C)

| Capacitance (pF) | Cap Code | Tolerance | X7R      |          |          |
|------------------|----------|-----------|----------|----------|----------|
|                  |          |           | 1H (50V) | 1E (25V) | 1C (16V) |
| 1,000            | 102      | K: ± 10%  | █        | █        | █        |
| 1,500            | 152      |           | █        | █        | █        |
| 2,200            | 222      |           | █        | █        | █        |
| 3,300            | 332      |           | █        | █        | █        |
| 4,700            | 472      |           | █        | █        | █        |
| 6,800            | 682      |           | █        | █        | █        |
| 10,000           | 103      |           | █        | █        | █        |
| 15,000           | 153      |           | █        | █        | █        |
| 22,000           | 223      |           | █        | █        | █        |
| 33,000           | 333      |           | █        | █        | █        |
| 47,000           | 473      |           | █        | █        | █        |
| 68,000           | 683      |           | █        | █        | █        |
| 100,000          | 104      |           | █        | █        | █        |

Standard Thickness 0.50 mm


**Capacitance  
Range Table**
**CGJ2 [EIA CC0402]**
**Class 1 (Temperature Compensating)**

Temperature Characteristics: C0G (-55 to 125°C, 0±30 ppm/°C)

| TDK Part Number<br>(Ordering Code) | Temperature<br>Characteristics | Rated<br>Voltage | Capacitance<br>(pF) | Capacitance<br>Tolerance | Thickness<br>(mm) |
|------------------------------------|--------------------------------|------------------|---------------------|--------------------------|-------------------|
| CGJ2B2C0G1H101J                    | C0G                            | 50V              | 100                 | ± 5%                     | 0.50 ± 0.05       |
| CGJ2B2C0G1H121J                    | C0G                            | 50V              | 120                 | ± 5%                     | 0.50 ± 0.05       |
| CGJ2B2C0G1H151J                    | C0G                            | 50V              | 150                 | ± 5%                     | 0.50 ± 0.05       |
| CGJ2B2C0G1H181J                    | C0G                            | 50V              | 180                 | ± 5%                     | 0.50 ± 0.05       |
| CGJ2B2C0G1H221J                    | C0G                            | 50V              | 220                 | ± 5%                     | 0.50 ± 0.05       |
| CGJ2B2C0G1H271J                    | C0G                            | 50V              | 270                 | ± 5%                     | 0.50 ± 0.05       |
| CGJ2B2C0G1H331J                    | C0G                            | 50V              | 330                 | ± 5%                     | 0.50 ± 0.05       |
| CGJ2B2C0G1H391J                    | C0G                            | 50V              | 390                 | ± 5%                     | 0.50 ± 0.05       |
| CGJ2B2C0G1H471J                    | C0G                            | 50V              | 470                 | ± 5%                     | 0.50 ± 0.05       |
| CGJ2B2C0G1H561J                    | C0G                            | 50V              | 560                 | ± 5%                     | 0.50 ± 0.05       |
| CGJ2B2C0G1H681J                    | C0G                            | 50V              | 680                 | ± 5%                     | 0.50 ± 0.05       |
| CGJ2B2C0G1H821J                    | C0G                            | 50V              | 820                 | ± 5%                     | 0.50 ± 0.05       |
| CGJ2B2C0G1H102J                    | C0G                            | 50V              | 1,000               | ± 5%                     | 0.50 ± 0.05       |


**Capacitance  
Range Table**
**CGJ2 [EIA CC0402]**
**Class 2 (Temperature Stable)**

Temperature Characteristics: X7R (-55 to +125°C, ±15%)

| TDK Part Number<br>(Ordering Code) | Temperature<br>Characteristics | Rated<br>Voltage | Capacitance<br>(pF) | Capacitance<br>Tolerance | Thickness<br>(mm) |
|------------------------------------|--------------------------------|------------------|---------------------|--------------------------|-------------------|
| CGJ2B2X7R1H102K                    | X7R                            | 50V              | 1,000               | ± 10%                    | 0.50 ± 0.05       |
| CGJ2B2X7R1H152K                    | X7R                            | 50V              | 1,500               | ± 10%                    | 0.50 ± 0.05       |
| CGJ2B2X7R1H222K                    | X7R                            | 50V              | 2,200               | ± 10%                    | 0.50 ± 0.05       |
| CGJ2B2X7R1H332K                    | X7R                            | 50V              | 3,300               | ± 10%                    | 0.50 ± 0.05       |
| CGJ2B2X7R1H472K                    | X7R                            | 50V              | 4,700               | ± 10%                    | 0.50 ± 0.05       |
| CGJ2B2X7R1H682K                    | X7R                            | 50V              | 6,800               | ± 10%                    | 0.50 ± 0.05       |
| CGJ2B2X7R1E102K                    | X7R                            | 25V              | 1,000               | ± 10%                    | 0.50 ± 0.05       |
| CGJ2B2X7R1E152K                    | X7R                            | 25V              | 1,500               | ± 10%                    | 0.50 ± 0.05       |
| CGJ2B2X7R1E222K                    | X7R                            | 25V              | 2,200               | ± 10%                    | 0.50 ± 0.05       |
| CGJ2B2X7R1E332K                    | X7R                            | 25V              | 3,300               | ± 10%                    | 0.50 ± 0.05       |
| CGJ2B2X7R1E472K                    | X7R                            | 25V              | 4,700               | ± 10%                    | 0.50 ± 0.05       |
| CGJ2B2X7R1E682K                    | X7R                            | 25V              | 6,800               | ± 10%                    | 0.50 ± 0.05       |
| CGJ2B2X7R1E103K                    | X7R                            | 25V              | 10,000              | ± 10%                    | 0.50 ± 0.05       |
| CGJ2B2X7R1E153K                    | X7R                            | 25V              | 15,000              | ± 10%                    | 0.50 ± 0.05       |
| CGJ2B2X7R1E223K                    | X7R                            | 25V              | 22,000              | ± 10%                    | 0.50 ± 0.05       |
| CGJ2B2X7R1E333K                    | X7R                            | 25V              | 33,000              | ± 10%                    | 0.50 ± 0.05       |
| CGJ2B2X7R1E473K                    | X7R                            | 25V              | 47,000              | ± 10%                    | 0.50 ± 0.05       |
| CGJ2B2X7R1C102K                    | X7R                            | 16V              | 1,000               | ± 10%                    | 0.50 ± 0.05       |
| CGJ2B2X7R1C152K                    | X7R                            | 16V              | 1,500               | ± 10%                    | 0.50 ± 0.05       |
| CGJ2B2X7R1C222K                    | X7R                            | 16V              | 2,200               | ± 10%                    | 0.50 ± 0.05       |
| CGJ2B2X7R1C332K                    | X7R                            | 16V              | 3,300               | ± 10%                    | 0.50 ± 0.05       |
| CGJ2B2X7R1C472K                    | X7R                            | 16V              | 4,700               | ± 10%                    | 0.50 ± 0.05       |
| CGJ2B2X7R1C682K                    | X7R                            | 16V              | 6,800               | ± 10%                    | 0.50 ± 0.05       |
| CGJ2B2X7R1C103K                    | X7R                            | 16V              | 10,000              | ± 10%                    | 0.50 ± 0.05       |
| CGJ2B2X7R1C153K                    | X7R                            | 16V              | 15,000              | ± 10%                    | 0.50 ± 0.05       |
| CGJ2B2X7R1C223K                    | X7R                            | 16V              | 22,000              | ± 10%                    | 0.50 ± 0.05       |
| CGJ2B2X7R1C333K                    | X7R                            | 16V              | 33,000              | ± 10%                    | 0.50 ± 0.05       |
| CGJ2B2X7R1C473K                    | X7R                            | 16V              | 47,000              | ± 10%                    | 0.50 ± 0.05       |
| CGJ2B2X7R1C683K                    | X7R                            | 16V              | 68,000              | ± 10%                    | 0.50 ± 0.05       |
| CGJ2B2X7R1C104K                    | X7R                            | 16V              | 100,000             | ± 10%                    | 0.50 ± 0.05       |



## Capacitance Range Chart

# CGJ3 [EIA CC0603]

### Capacitance Range Chart

Temperature Characteristics: C0G (0±30 ppm/°C)

Rated Voltage: 50V (1H)

| Capacitance (pF) | Cap Code | Tolerance | C0G      |
|------------------|----------|-----------|----------|
|                  |          |           | 1H (50V) |
| 270              | 271      | J: ± 5%   | █        |
| 330              | 331      |           | █        |
| 390              | 391      |           | █        |
| 470              | 471      |           | █        |
| 560              | 561      |           | █        |
| 680              | 681      |           | █        |
| 820              | 821      |           | █        |
| 1,000            | 102      |           | █        |
| 1,200            | 122      |           | █        |
| 1,500            | 152      |           | █        |
| 1,800            | 182      |           | █        |
| 2,200            | 222      |           | █        |
| 2,700            | 272      |           | █        |
| 3,300            | 332      |           | █        |
| 3,900            | 392      |           | █        |
| 4,700            | 472      |           | █        |
| 5,600            | 562      |           | █        |
| 6,800            | 682      |           | █        |
| 8,200            | 822      |           | █        |
| 10,000           | 103      |           | █        |

**Standard Thickness**  
█ 0.80 mm

### Capacitance Range Chart

Temperature Characteristics: X7R (± 15%)

Rated Voltage: 50V (1H), 25V (1E), 16V (1C), 10V (1A), 6.3V (0J)

| Capacitance (pF) | Cap Code | Tolerance | X7R      |          |          |          |           |
|------------------|----------|-----------|----------|----------|----------|----------|-----------|
|                  |          |           | 1H (50V) | 1E (25V) | 1C (16V) | 1A (10V) | 0J (6.3V) |
| 10,000           | 103      | K: ± 10%  | █        | █        | █        |          |           |
| 15,000           | 153      |           | █        | █        | █        |          |           |
| 22,000           | 223      |           | █        | █        | █        |          |           |
| 33,000           | 333      |           | █        | █        | █        |          |           |
| 47,000           | 473      |           | █        | █        | █        |          |           |
| 68,000           | 683      |           | █        | █        | █        |          |           |
| 100,000          | 104      |           | █        | █        | █        |          |           |
| 330,000          | 334      |           | █        |          |          |          | █         |
| 470,000          | 474      |           | █        |          |          |          | █         |
| 680,000          | 684      |           | █        |          |          |          | █         |
| 1,000,000        | 105      |           | █        |          |          |          | █         |

**Standard Thickness**  
█ 0.80 mm



## Capacitance Range Table

# CGJ3 [EIA CC0603]

### Class 1 (Temperature Compensating)

Temperature Characteristics: C0G (-55 to 125°C, 0±30 ppm/°C)

| TDK Part Number<br>(Ordering Code) | Temperature<br>Characteristics | Rated<br>Voltage | Capacitance<br>(pF) | Capacitance<br>Tolerance | Thickness<br>(mm) |
|------------------------------------|--------------------------------|------------------|---------------------|--------------------------|-------------------|
| CGJ3E2C0G1H271J                    | C0G                            | 50V              | 270                 | ± 5%                     | 0.80 ± 0.07       |
| CGJ3E2C0G1H331J                    | C0G                            | 50V              | 330                 | ± 5%                     | 0.80 ± 0.07       |
| CGJ3E2C0G1H391J                    | C0G                            | 50V              | 390                 | ± 5%                     | 0.80 ± 0.07       |
| CGJ3E2C0G1H471J                    | C0G                            | 50V              | 470                 | ± 5%                     | 0.80 ± 0.07       |
| CGJ3E2C0G1H561J                    | C0G                            | 50V              | 560                 | ± 5%                     | 0.80 ± 0.07       |
| CGJ3E2C0G1H681J                    | C0G                            | 50V              | 680                 | ± 5%                     | 0.80 ± 0.07       |
| CGJ3E2C0G1H821J                    | C0G                            | 50V              | 820                 | ± 5%                     | 0.80 ± 0.07       |
| CGJ3E2C0G1H102J                    | C0G                            | 50V              | 1,000               | ± 5%                     | 0.80 ± 0.07       |
| CGJ3E2C0G1H122J                    | C0G                            | 50V              | 1,200               | ± 5%                     | 0.80 ± 0.07       |
| CGJ3E2C0G1H152J                    | C0G                            | 50V              | 1,500               | ± 5%                     | 0.80 ± 0.07       |
| CGJ3E2C0G1H182J                    | C0G                            | 50V              | 1,800               | ± 5%                     | 0.80 ± 0.07       |
| CGJ3E2C0G1H222J                    | C0G                            | 50V              | 2,200               | ± 5%                     | 0.80 ± 0.07       |
| CGJ3E2C0G1H272J                    | C0G                            | 50V              | 2,700               | ± 5%                     | 0.80 ± 0.07       |
| CGJ3E2C0G1H332J                    | C0G                            | 50V              | 3,300               | ± 5%                     | 0.80 ± 0.07       |
| CGJ3E2C0G1H392J                    | C0G                            | 50V              | 3,900               | ± 5%                     | 0.80 ± 0.07       |
| CGJ3E2C0G1H472J                    | C0G                            | 50V              | 4,700               | ± 5%                     | 0.80 ± 0.07       |
| CGJ3E2C0G1H562J                    | C0G                            | 50V              | 5,600               | ± 5%                     | 0.80 ± 0.07       |
| CGJ3E2C0G1H682J                    | C0G                            | 50V              | 6,800               | ± 5%                     | 0.80 ± 0.07       |
| CGJ3E2C0G1H822J                    | C0G                            | 50V              | 8,200               | ± 5%                     | 0.80 ± 0.07       |
| CGJ3E2C0G1H103J                    | C0G                            | 50V              | 10,000              | ± 5%                     | 0.80 ± 0.07       |




**Capacitance  
Range Table**
**CGJ3 [EIA CC0603]**
**Class 2 (Temperature Stable)**

Temperature Characteristics: X7R (-55 to +125°C, ±15%)

| TDK Part Number<br>(Ordering Code) | Temperature<br>Characteristics | Rated<br>Voltage | Capacitance<br>(pF) | Capacitance<br>Tolerance | Thickness<br>(mm) |
|------------------------------------|--------------------------------|------------------|---------------------|--------------------------|-------------------|
| CGJ3E2X7R1H103K                    | X7R                            | 50V              | 10,000              | ± 10%                    | 0.80 ± 0.07       |
| CGJ3E2X7R1H153K                    | X7R                            | 50V              | 15,000              | ± 10%                    | 0.80 ± 0.07       |
| CGJ3E2X7R1H223K                    | X7R                            | 50V              | 22,000              | ± 10%                    | 0.80 ± 0.07       |
| CGJ3E2X7R1H333K                    | X7R                            | 50V              | 33,000              | ± 10%                    | 0.80 ± 0.07       |
| CGJ3E2X7R1H473K                    | X7R                            | 50V              | 47,000              | ± 10%                    | 0.80 ± 0.07       |
| CGJ3E2X7R1H683K                    | X7R                            | 50V              | 68,000              | ± 10%                    | 0.80 ± 0.07       |
| CGJ3E2X7R1H104K                    | X7R                            | 50V              | 100,000             | ± 10%                    | 0.80 ± 0.10       |
| CGJ3E2X7R1E103K                    | X7R                            | 25V              | 10,000              | ± 10%                    | 0.80 ± 0.07       |
| CGJ3E2X7R1E153K                    | X7R                            | 25V              | 15,000              | ± 10%                    | 0.80 ± 0.07       |
| CGJ3E2X7R1E223K                    | X7R                            | 25V              | 22,000              | ± 10%                    | 0.80 ± 0.07       |
| CGJ3E2X7R1E333K                    | X7R                            | 25V              | 33,000              | ± 10%                    | 0.80 ± 0.07       |
| CGJ3E2X7R1E473K                    | X7R                            | 25V              | 47,000              | ± 10%                    | 0.80 ± 0.07       |
| CGJ3E2X7R1E683K                    | X7R                            | 25V              | 68,000              | ± 10%                    | 0.80 ± 0.07       |
| CGJ3E2X7R1E104K                    | X7R                            | 25V              | 100,000             | ± 10%                    | 0.80 ± 0.07       |
| CGJ3E2X7R1C103K                    | X7R                            | 16V              | 10,000              | ± 10%                    | 0.80 ± 0.07       |
| CGJ3E2X7R1C153K                    | X7R                            | 16V              | 15,000              | ± 10%                    | 0.80 ± 0.07       |
| CGJ3E2X7R1C223K                    | X7R                            | 16V              | 22,000              | ± 10%                    | 0.80 ± 0.07       |
| CGJ3E2X7R1C333K                    | X7R                            | 16V              | 33,000              | ± 10%                    | 0.80 ± 0.07       |
| CGJ3E2X7R1C473K                    | X7R                            | 16V              | 47,000              | ± 10%                    | 0.80 ± 0.07       |
| CGJ3E2X7R1C683K                    | X7R                            | 16V              | 68,000              | ± 10%                    | 0.80 ± 0.07       |
| CGJ3E2X7R1C104K                    | X7R                            | 16V              | 100,000             | ± 10%                    | 0.80 ± 0.07       |
| CGJ3E2X7R1A334K                    | X7R                            | 10V              | 330,000             | ± 10%                    | 0.80 ± 0.07       |
| CGJ3E2X7R1A474K                    | X7R                            | 10V              | 470,000             | ± 10%                    | 0.80 ± 0.07       |
| CGJ3E2X7R1A684K                    | X7R                            | 10V              | 680,000             | ± 10%                    | 0.80 ± 0.07       |
| CGJ3E2X7R1A105K                    | X7R                            | 10V              | 1,000,000           | ± 10%                    | 0.80 ± 0.10       |
| CGJ3E2X7R0J334K                    | X7R                            | 6.3V             | 330,000             | ± 10%                    | 0.80 ± 0.07       |
| CGJ3E2X7R0J474K                    | X7R                            | 6.3V             | 470,000             | ± 10%                    | 0.80 ± 0.07       |
| CGJ3E2X7R0J684K                    | X7R                            | 6.3V             | 680,000             | ± 10%                    | 0.80 ± 0.07       |
| CGJ3E2X7R0J105K                    | X7R                            | 6.3V             | 1,000,000           | ± 10%                    | 0.80 ± 0.10       |



## Capacitance Range Chart

## CGJ4 [EIA CC0805]

### Capacitance Range Chart

Temperature Characteristics: C0G (0±30 ppm/°C)

Rated Voltage: 50V (1H)

| Capacitance (pF) | Cap Code | Tolerance | C0G      |
|------------------|----------|-----------|----------|
|                  |          |           | 1H (50V) |
| 680              | 681      | J: ± 5%   | █        |
| 820              | 821      |           |          |
| 1,000            | 102      |           |          |
| 1,200            | 122      |           |          |
| 1,500            | 152      |           |          |
| 1,800            | 182      |           |          |
| 2,200            | 222      |           |          |
| 2,700            | 272      |           |          |
| 3,300            | 332      |           |          |
| 3,900            | 392      |           |          |
| 4,700            | 472      |           |          |
| 5,600            | 562      |           |          |
| 6,800            | 682      |           |          |
| 8,200            | 822      |           |          |
| 10,000           | 103      |           |          |
| 15,000           | 153      |           |          |
| 22,000           | 223      |           |          |
| 33,000           | 333      |           |          |

#### Standard Thickness

- 0.60 mm
- 0.85 mm
- 1.25 mm

### Capacitance Range Chart

Temperature Characteristics: X7R (± 15%)

Rated Voltage: 50V (1H), 25V (1E), 16V (1C), 10V (1A), 6.3V (0J)

| Capacitance (pF) | Cap Code | Tolerance | X7R      |          |          |          |           |
|------------------|----------|-----------|----------|----------|----------|----------|-----------|
|                  |          |           | 1H (50V) | 1E (25V) | 1C (16V) | 1A (10V) | 0J (6.3V) |
| 33,000           | 333      | K: ± 10%  | █        | █        | █        | █        | █         |
| 47,000           | 473      |           |          |          |          |          |           |
| 68,000           | 683      |           |          |          |          |          |           |
| 100,000          | 104      |           |          |          |          |          |           |
| 150,000          | 154      |           |          |          |          |          |           |
| 220,000          | 224      |           |          |          |          |          |           |
| 330,000          | 334      |           |          |          |          |          |           |
| 470,000          | 474      |           |          |          |          |          |           |
| 680,000          | 684      |           |          |          |          |          |           |
| 1,000,000        | 105      |           |          |          |          |          |           |
| 1,500,000        | 155      |           |          |          |          |          |           |
| 2,200,000        | 225      |           |          |          |          |          |           |
| 3,300,000        | 335      |           |          |          |          |          |           |
| 4,700,000        | 475      |           |          |          |          |          |           |

#### Standard Thickness

- 1.25 mm


**Capacitance  
Range Table**
**CGJ4 [EIA CC0805]**
**Class 1 (Temperature Compensating)**

Temperature Characteristics: C0G (-55 to 125°C, 0±30 ppm/°C)

| TDK Part Number<br>(Ordering Code) | Temperature<br>Characteristics | Rated<br>Voltage | Capacitance<br>(pF) | Capacitance<br>Tolerance | Thickness<br>(mm) |
|------------------------------------|--------------------------------|------------------|---------------------|--------------------------|-------------------|
| CGJ4C2C0G1H681J                    | C0G                            | 50V              | 680                 | ± 5%                     | 0.60 ± 0.10       |
| CGJ4C2C0G1H821J                    | C0G                            | 50V              | 820                 | ± 5%                     | 0.60 ± 0.10       |
| CGJ4C2C0G1H102J                    | C0G                            | 50V              | 1,000               | ± 5%                     | 0.60 ± 0.10       |
| CGJ4C2C0G1H122J                    | C0G                            | 50V              | 1,200               | ± 5%                     | 0.60 ± 0.10       |
| CGJ4C2C0G1H152J                    | C0G                            | 50V              | 1,500               | ± 5%                     | 0.60 ± 0.10       |
| CGJ4C2C0G1H182J                    | C0G                            | 50V              | 1,800               | ± 5%                     | 0.60 ± 0.10       |
| CGJ4C2C0G1H222J                    | C0G                            | 50V              | 2,200               | ± 5%                     | 0.60 ± 0.10       |
| CGJ4C2C0G1H272J                    | C0G                            | 50V              | 2,700               | ± 5%                     | 0.60 ± 0.10       |
| CGJ4C2C0G1H332J                    | C0G                            | 50V              | 3,300               | ± 5%                     | 0.60 ± 0.10       |
| CGJ4C2C0G1H392J                    | C0G                            | 50V              | 3,900               | ± 5%                     | 0.60 ± 0.10       |
| CGJ4C2C0G1H472J                    | C0G                            | 50V              | 4,700               | ± 5%                     | 0.60 ± 0.10       |
| CGJ4C2C0G1H562J                    | C0G                            | 50V              | 5,600               | ± 5%                     | 0.60 ± 0.10       |
| CGJ4C2C0G1H682J                    | C0G                            | 50V              | 6,800               | ± 5%                     | 0.60 ± 0.10       |
| CGJ4C2C0G1H822J                    | C0G                            | 50V              | 8,200               | ± 5%                     | 0.60 ± 0.10       |
| CGJ4C2C0G1H103J                    | C0G                            | 50V              | 10,000              | ± 5%                     | 0.60 ± 0.10       |
| CGJ4F2C0G1H153J                    | C0G                            | 50V              | 15,000              | ± 5%                     | 0.85 +0.02/-0.10  |
| CGJ4J2C0G1H223J                    | C0G                            | 50V              | 22,000              | ± 5%                     | 1.25 ± 0.10       |
| CGJ4J2C0G1H333J                    | C0G                            | 50V              | 33,000              | ± 5%                     | 1.25 ± 0.20       |


**Capacitance  
Range Table**
**CGJ4 [EIA CC0805]**
**Class 2 (Temperature Stable)**

Temperature Characteristics: X7R (-55 to +125°C, ±15%)

| TDK Part Number<br>(Ordering Code) | Temperature<br>Characteristics | Rated<br>Voltage | Capacitance<br>(pF) | Capacitance<br>Tolerance | Thickness<br>(mm) |
|------------------------------------|--------------------------------|------------------|---------------------|--------------------------|-------------------|
| CGJ4J2X7R1H333K                    | X7R                            | 50V              | 33,000              | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R1H473K                    | X7R                            | 50V              | 47,000              | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R1H683K                    | X7R                            | 50V              | 68,000              | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R1H104K                    | X7R                            | 50V              | 100,000             | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R1H154K                    | X7R                            | 50V              | 150,000             | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R1H224K                    | X7R                            | 50V              | 220,000             | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R1H334K                    | X7R                            | 50V              | 330,000             | ± 10%                    | 1.25 ± 0.20       |
| CGJ4J2X7R1E333K                    | X7R                            | 25V              | 33,000              | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R1E473K                    | X7R                            | 25V              | 47,000              | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R1E683K                    | X7R                            | 25V              | 68,000              | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R1E104K                    | X7R                            | 25V              | 100,000             | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R1E154K                    | X7R                            | 25V              | 150,000             | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R1E224K                    | X7R                            | 25V              | 220,000             | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R1E334K                    | X7R                            | 25V              | 330,000             | ± 10%                    | 1.25 ± 0.20       |
| CGJ4J2X7R1E474K                    | X7R                            | 25V              | 470,000             | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R1E684K                    | X7R                            | 25V              | 680,000             | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R1E105K                    | X7R                            | 25V              | 1,000,000           | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R1C333K                    | X7R                            | 16V              | 33,000              | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R1C473K                    | X7R                            | 16V              | 47,000              | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R1C683K                    | X7R                            | 16V              | 68,000              | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R1C104K                    | X7R                            | 16V              | 100,000             | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R1C154K                    | X7R                            | 16V              | 150,000             | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R1C224K                    | X7R                            | 16V              | 220,000             | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R1C334K                    | X7R                            | 16V              | 330,000             | ± 10%                    | 1.25 ± 0.20       |
| CGJ4J2X7R1C474K                    | X7R                            | 16V              | 470,000             | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R1C684K                    | X7R                            | 16V              | 680,000             | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R1C105K                    | X7R                            | 16V              | 1,000,000           | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R1A224K                    | X7R                            | 10V              | 220,000             | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R1A334K                    | X7R                            | 10V              | 330,000             | ± 10%                    | 1.25 ± 0.20       |
| CGJ4J2X7R1A474K                    | X7R                            | 10V              | 470,000             | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R1A684K                    | X7R                            | 10V              | 680,000             | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R1A105K                    | X7R                            | 10V              | 1,000,000           | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R1A155K                    | X7R                            | 10V              | 1,500,000           | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R1A225K                    | X7R                            | 10V              | 2,200,000           | ± 10%                    | 1.25 ± 0.20       |
| CGJ4J2X7R1A335K                    | X7R                            | 10V              | 3,300,000           | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R1A475K                    | X7R                            | 10V              | 4,700,000           | ± 10%                    | 1.25 ± 0.20       |
| CGJ4J2X7R0J224K                    | X7R                            | 6.3V             | 220,000             | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R0J334K                    | X7R                            | 6.3V             | 330,000             | ± 10%                    | 1.25 ± 0.20       |
| CGJ4J2X7R0J474K                    | X7R                            | 6.3V             | 470,000             | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R0J684K                    | X7R                            | 6.3V             | 680,000             | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R0J105K                    | X7R                            | 6.3V             | 1,000,000           | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R0J155K                    | X7R                            | 6.3V             | 1,500,000           | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R0J225K                    | X7R                            | 6.3V             | 2,200,000           | ± 10%                    | 1.25 ± 0.20       |
| CGJ4J2X7R0J335K                    | X7R                            | 6.3V             | 3,300,000           | ± 10%                    | 1.25 ± 0.10       |
| CGJ4J2X7R0J475K                    | X7R                            | 6.3V             | 4,700,000           | ± 10%                    | 1.25 ± 0.20       |




**Capacitance Range Chart**

**CGJ5 [EIA CC1206]**

**Capacitance Range Chart**

Temperature Characteristics: C0G (0±30 ppm/°C)  
 Rated Voltage: 50V (1H)

| Capacitance (pF) | Cap Code | Tolerance | C0G      |
|------------------|----------|-----------|----------|
|                  |          |           | 1H (50V) |
| 3,900            | 392      | J: ± 5%   |          |
| 4,700            | 472      |           |          |
| 5,600            | 562      |           |          |
| 6,800            | 682      |           |          |
| 8,200            | 822      |           |          |
| 10,000           | 103      |           |          |
| 15,000           | 153      |           |          |
| 22,000           | 223      |           |          |
| 33,000           | 333      |           |          |
| 47,000           | 473      |           |          |
| 68,000           | 683      |           |          |
| 100,000          | 104      |           |          |



**Capacitance Range Chart**

Temperature Characteristics: X7R (± 15%)  
 Rated Voltage: 25V (1E), 16V (1C), 10V (1A), 6.3V (0J)

| Capacitance (pF) | Cap Code | Tolerance | X7R      |          |          |           |
|------------------|----------|-----------|----------|----------|----------|-----------|
|                  |          |           | 1E (25V) | 1C (16V) | 1A (10V) | 0J (6.3V) |
| 1,500,000        | 155      | K: ± 10%  |          |          |          |           |
| 2,200,000        | 225      |           |          |          |          |           |
| 3,300,000        | 335      |           |          |          |          |           |
| 4,700,000        | 475      |           |          |          |          |           |
| 6,800,000        | 685      |           |          |          |          |           |
| 10,000,000       | 106      |           |          |          |          |           |




**Capacitance  
Range Table**
**CGJ5 [EIA CC1206]**
**Class 1 (Temperature Compensating)**

Temperature Characteristics: C0G (-55 to 125°C, 0±30 ppm/°C)

| TDK Part Number<br>(Ordering Code) | Temperature<br>Characteristics | Rated<br>Voltage | Capacitance<br>(pF) | Capacitance<br>Tolerance | Thickness<br>(mm) |
|------------------------------------|--------------------------------|------------------|---------------------|--------------------------|-------------------|
| CGJ5C2C0G1H392J                    | C0G                            | 50V              | 3,900               | ± 5%                     | 0.60 ± 0.10       |
| CGJ5C2C0G1H472J                    | C0G                            | 50V              | 4,700               | ± 5%                     | 0.60 ± 0.10       |
| CGJ5C2C0G1H562J                    | C0G                            | 50V              | 5,600               | ± 5%                     | 0.60 ± 0.10       |
| CGJ5C2C0G1H682J                    | C0G                            | 50V              | 6,800               | ± 5%                     | 0.60 ± 0.10       |
| CGJ5C2C0G1H822J                    | C0G                            | 50V              | 8,200               | ± 5%                     | 0.60 ± 0.10       |
| CGJ5C2C0G1H103J                    | C0G                            | 50V              | 10,000              | ± 5%                     | 0.60 ± 0.10       |
| CGJ5C2C0G1H153J                    | C0G                            | 50V              | 15,000              | ± 5%                     | 0.60 ± 0.10       |
| CGJ5C2C0G1H223J                    | C0G                            | 50V              | 22,000              | ± 5%                     | 0.60 ± 0.10       |
| CGJ5F2C0G1H333J                    | C0G                            | 50V              | 33,000              | ± 5%                     | 0.85 +0.02/-0.10  |
| CGJ5H2C0G1H473J                    | C0G                            | 50V              | 47,000              | ± 5%                     | 1.15 ± 0.10       |
| CGJ5L2C0G1H683J                    | C0G                            | 50V              | 68,000              | ± 5%                     | 1.60 +0.20/-0.10  |
| CGJ5L2C0G1H104J                    | C0G                            | 50V              | 100,000             | ± 5%                     | 1.60 +0.20/-0.10  |

**Class 2 (Temperature Stable)**

Temperature Characteristics: X7R (-55 to +125°C, ±15%)


| TDK Part Number<br>(Ordering Code) | Temperature<br>Characteristics | Rated<br>Voltage | Capacitance<br>(pF) | Capacitance<br>Tolerance | Thickness<br>(mm) |
|------------------------------------|--------------------------------|------------------|---------------------|--------------------------|-------------------|
| CGJ5L2X7R1E155K                    | X7R                            | 25V              | 1,500,000           | ± 10%                    | 1.60 ± 0.10       |
| CGJ5L2X7R1E225K                    | X7R                            | 25V              | 2,200,000           | ± 10%                    | 1.60 +0.20/-0.10  |
| CGJ5L2X7R1C155K                    | X7R                            | 16V              | 1,500,000           | ± 10%                    | 1.60 ± 0.10       |
| CGJ5L2X7R1C225K                    | X7R                            | 16V              | 2,200,000           | ± 10%                    | 1.60 +0.20/-0.10  |
| CGJ5L2X7R1C335K                    | X7R                            | 16V              | 3,300,000           | ± 10%                    | 1.60 ± 0.10       |
| CGJ5L2X7R1C475K                    | X7R                            | 16V              | 4,700,000           | ± 10%                    | 1.60 +0.20/-0.10  |
| CGJ5L2X7R1A155K                    | X7R                            | 10V              | 1,500,000           | ± 10%                    | 1.60 ± 0.10       |
| CGJ5L2X7R1A225K                    | X7R                            | 10V              | 2,200,000           | ± 10%                    | 1.60 +0.20/-0.10  |
| CGJ5L2X7R1A335K                    | X7R                            | 10V              | 3,300,000           | ± 10%                    | 1.60 ± 0.10       |
| CGJ5L2X7R1A475K                    | X7R                            | 10V              | 4,700,000           | ± 10%                    | 1.60 +0.20/-0.10  |
| CGJ5L2X7R1A685K                    | X7R                            | 10V              | 6,800,000           | ± 10%                    | 1.60 ± 0.10       |
| CGJ5L2X7R1A106K                    | X7R                            | 10V              | 10,000,000          | ± 10%                    | 1.60 +0.20/-0.10  |
| CGJ5L2X7R0J155K                    | X7R                            | 6.3V             | 1,500,000           | ± 10%                    | 1.60 ± 0.10       |
| CGJ5L2X7R0J225K                    | X7R                            | 6.3V             | 2,200,000           | ± 10%                    | 1.60 +0.20/-0.10  |
| CGJ5L2X7R0J335K                    | X7R                            | 6.3V             | 3,300,000           | ± 10%                    | 1.60 ± 0.10       |
| CGJ5L2X7R0J475K                    | X7R                            | 6.3V             | 4,700,000           | ± 10%                    | 1.60 +0.20/-0.10  |
| CGJ5L2X7R0J685K                    | X7R                            | 6.3V             | 6,800,000           | ± 10%                    | 1.60 ± 0.10       |
| CGJ5L2X7R0J106K                    | X7R                            | 6.3V             | 10,000,000          | ± 10%                    | 1.60 +0.20/-0.10  |



## Additional Information


# CGJ Series – Extended Life Capacitors

### • Shape & Dimensions



| Case Code |       |        | Dimensions (mm) |      |      |           |           |
|-----------|-------|--------|-----------------|------|------|-----------|-----------|
| Series    | JIS   | EIA    | L               | W    | T    | B         | G         |
| CGJ2      | C1005 | CC0402 | 1.00            | 0.50 | 0.50 | 0.10      | 0.30 min. |
| CGJ3      | C1608 | CC0603 | 1.60            | 0.80 | 0.80 | 0.20      | 0.50 min. |
| CGJ4      | C2012 | CC0805 | 2.00            | 1.25 | 0.60 | 0.20 min. | 0.50 min. |
|           |       |        |                 |      | 0.85 |           |           |
|           |       |        |                 |      | 1.25 |           |           |
| CGJ5      | C3216 | CC1206 | 3.20            | 1.60 | 0.60 | 0.20 min. | 1.00 min. |
|           |       |        |                 |      | 0.85 |           |           |
|           |       |        |                 |      | 1.15 |           |           |
|           |       |        |                 |      | 1.60 |           |           |

### • Inside Structure & Material System



| No. | NAME               | MATERIAL           |                    |
|-----|--------------------|--------------------|--------------------|
|     |                    | Class 1            | Class 2            |
| (1) | Ceramic Dielectric | CaZrO <sub>3</sub> | BaTiO <sub>3</sub> |
| (2) | Internal Electrode | Nickel (Ni)        |                    |
| (3) | Termination        | Copper (Cu)        |                    |
| (4) |                    | Nickel (Ni)        |                    |
| (5) |                    | Tin (Sn)           |                    |

### • Environmental Information

TDK Corporation established internal product environmental assurance standards that include the six hazardous substances banned by the EU RoHS Directive<sup>1</sup> enforced on July 1, 2006 along with additional substances independently banned by TDK and has successfully completed making general purpose electronic components conform to the RoHS Directive<sup>2</sup>.

1. Abbreviation for Restriction on Hazardous Substances, which refers to the regulation EU Directive 2002/95/EC on hazardous substances by the European Union (EU) effective from July 1, 2006. The Directive bans the use of six specific hazardous substances in electric and electronic devices and products handled within the EU. The six substances are lead, mercury, cadmium, hexavalent chromium, PBB (polybrominated biphenyls), and PBDE (polybrominated diphenyl ethers).
2. This means that, in conformity with the EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.

For REACH (SVHC : 15 substances according to ECHA / October 2008) : All TDK MLCC do not contain these 15 substances.

For European Directive 2000/53/CE and 2005/673/CE : Cadmium, Hexavalent Chromium, Mercury, Lead are not contained in all TDK MLCC.

For European Directive 2003/11/CE : Pentabromodiphenyl-ether, Octabromodiphenyl-ether are not contained in all TDK MLCC.



# TDK Sales Representatives Contact Information

South Bridge, LLC  
South Carolina, USA  
[Email: crystal@southbridge.net](mailto:crystal@southbridge.net)  
[Website: www.southbridge.net](http://www.southbridge.net)

South Bridge, LLC  
Alabama, USA  
[Email: sherrill@southbridge.net](mailto:sherrill@southbridge.net)  
[Website: www.southbridge.net](http://www.southbridge.net)

South Bridge, LLC  
Mississippi, USA  
[Email: sherrill@southbridge.net](mailto:sherrill@southbridge.net)  
[Website: www.southbridge.net](http://www.southbridge.net)

South Bridge, LLC  
North Carolina, USA  
[Email: crystal@southbridge.net](mailto:crystal@southbridge.net)  
[Website: www.southbridge.net](http://www.southbridge.net)

South Bridge, LLC  
Western Tennessee, USA  
[Email: sherrill@southbridge.net](mailto:sherrill@southbridge.net)  
[Website: www.southbridge.net](http://www.southbridge.net)

South Bridge, LLC  
Georgia, USA  
[Email: bobbi@southbridge.net](mailto:bobbi@southbridge.net)  
[Website: www.southbridge.net](http://www.southbridge.net)

South Bridge, LLC  
Eastern Tennessee, USA  
[Email: bobbi@southbridge.net](mailto:bobbi@southbridge.net)  
[Website: www.southbridge.net](http://www.southbridge.net)

South Bridge, LLC  
Florida, USA  
[Email: kim@southbridge.net](mailto:kim@southbridge.net)  
[Website: www.southbridge.net](http://www.southbridge.net)

Seltec Sales Corporation  
Missouri, USA  
[Email: christy\\_meyer@seltec-sales.com](mailto:christy_meyer@seltec-sales.com)  
[Website: www.seltecsales.com](http://www.seltecsales.com)

Seltec Sales Corporation  
Kansas, USA  
[Email: brian\\_young@seltec-sales.com](mailto:brian_young@seltec-sales.com)  
[Website: www.seltecsales.com](http://www.seltecsales.com)

Seltec Sales Corporation  
Southern Illinois, USA  
[Email: christy\\_meyer@seltec-sales.com](mailto:christy_meyer@seltec-sales.com)  
[Website: www.seltecsales.com](http://www.seltecsales.com)

Seltec Sales Corporation  
Nebraska, USA  
[Email: brian\\_young@seltec-sales.com](mailto:brian_young@seltec-sales.com)  
[Website: www.seltecsales.com](http://www.seltecsales.com)

Quad State Sales and Marketing  
Texas, USA  
[Email: kbrayman@quadstatesales.com](mailto:kbrayman@quadstatesales.com)  
[Website: www.quadstatesales.com](http://www.quadstatesales.com)

Quad State Sales and Marketing  
Oklahoma, USA  
[Email: kbrayman@quadstatesales.com](mailto:kbrayman@quadstatesales.com)  
[Website: www.quadstatesales.com](http://www.quadstatesales.com)

Quad State Sales and Marketing  
Arkansas, USA  
[Email: kbrayman@quadstatesales.com](mailto:kbrayman@quadstatesales.com)  
[Website: www.quadstatesales.com](http://www.quadstatesales.com)

Quad State Sales and Marketing  
Louisiana, USA  
[Email: kbrayman@quadstatesales.com](mailto:kbrayman@quadstatesales.com)  
[Website: www.quadstatesales.com](http://www.quadstatesales.com)

Procyon Technical Sales  
Southern Nevada, USA  
[Email: lfisher@procyonsales.com](mailto:lfisher@procyonsales.com)  
[Website: www.procyonsales.com](http://www.procyonsales.com)

Procyon Technical Sales  
New Mexico, USA  
[Email: lfisher@procyonsales.com](mailto:lfisher@procyonsales.com)  
[Website: www.procyonsales.com](http://www.procyonsales.com)

Procyon Technical Sales  
New Mexico, USA  
[Email: lfisher@procyonsales.com](mailto:lfisher@procyonsales.com)  
[Website: www.procyonsales.com](http://www.procyonsales.com)

Procyon Technical Sales  
Arizona, USA  
[Email: lfisher@procyonsales.com](mailto:lfisher@procyonsales.com)  
[Website: www.procyonsales.com](http://www.procyonsales.com)

Procyon Technical Sales  
Southern California, USA  
[Email: lfisher@procyonsales.com](mailto:lfisher@procyonsales.com)  
[Website: www.procyonsales.com](http://www.procyonsales.com)

Paragon Electronic Systems  
Vermont, USA  
[Email: sales@paragonelect.com](mailto:sales@paragonelect.com)  
[Website: www.paragonelect.com](http://www.paragonelect.com)

Paragon Electronic Systems  
Rhode Island, USA  
[Email: sales@paragonelect.com](mailto:sales@paragonelect.com)  
[Website: www.paragonelect.com](http://www.paragonelect.com)

Paragon Electronic Systems  
New Hampshire, USA  
[Email: sales@paragonelect.com](mailto:sales@paragonelect.com)  
[Website: www.paragonelect.com](http://www.paragonelect.com)

Paragon Electronic Systems  
Maine, USA  
[Email: sales@paragonelect.com](mailto:sales@paragonelect.com)  
[Website: www.paragonelect.com](http://www.paragonelect.com)

Paragon Electronic Systems  
Massachusetts, USA  
[Email: sales@paragonelect.com](mailto:sales@paragonelect.com)  
[Website: www.paragonelect.com](http://www.paragonelect.com)

Paragon Electronic Systems  
Connecticut, USA  
[Email: sales@paragonelect.com](mailto:sales@paragonelect.com)  
[Website: www.paragonelect.com](http://www.paragonelect.com)

Omega Electronic Sales, Inc.  
Southern New Jersey, USA  
[Email: office@omegasales.com](mailto:office@omegasales.com)  
[Website: www.omegasales.com](http://www.omegasales.com)

Omega Electronic Sales, Inc.  
Delaware, USA  
[Email: office@omegasales.com](mailto:office@omegasales.com)  
[Website: www.omegasales.com](http://www.omegasales.com)

Omega Electronic Sales, Inc.  
Eastern Pennsylvania, USA  
[Email: office@omegasales.com](mailto:office@omegasales.com)  
[Website: www.omegasales.com](http://www.omegasales.com)

Mel Foster Company  
Iowa, USA  
[Email: sonja@melfoster.com](mailto:sonja@melfoster.com)  
[Website: www.melfoster.com](http://www.melfoster.com)

Mel Foster Company  
North Dakota, USA  
[Email: kristine@melfoster.com](mailto:kristine@melfoster.com)  
[Website: www.melfoster.com](http://www.melfoster.com)

Mel Foster Company  
South Dakota, USA  
[Email: kristine@melfoster.com](mailto:kristine@melfoster.com)  
[Website: www.melfoster.com](http://www.melfoster.com)

Mel Foster Company  
Minnesota, USA  
[Email: kristine@melfoster.com](mailto:kristine@melfoster.com)  
[Website: www.melfoster.com](http://www.melfoster.com)

Mel Foster Company  
Northwest Wisconsin, USA  
[Email: kristine@melfoster.com](mailto:kristine@melfoster.com)  
[Website: www.melfoster.com](http://www.melfoster.com)

Luscombe Engineering Company  
Northern California, USA  
[Email: dbrown@lecsf.com](mailto:dbrown@lecsf.com)  
[Website: www.lecsf.com](http://www.lecsf.com)

Luscombe Engineering Company  
Northern Nevada, All products, USA  
[Email: dbrown@lecsf.com](mailto:dbrown@lecsf.com)  
[Website: www.lecsf.com](http://www.lecsf.com)

Innovatech Rocky Mountains  
Colorado, USA  
[Email: ggoodenow@innovatechrm.com](mailto:ggoodenow@innovatechrm.com)  
[Website: www.innovatechrm.com](http://www.innovatechrm.com)

Innovatech Rocky Mountains  
Utah, USA  
[Email: ggoodenow@innovatechrm.com](mailto:ggoodenow@innovatechrm.com)  
[Website: www.innovatechrm.com](http://www.innovatechrm.com)

Innovatech Rocky Mountains  
Montana, USA  
[Email: ggoodenow@innovatechrm.com](mailto:ggoodenow@innovatechrm.com)  
[Website: www.innovatechrm.com](http://www.innovatechrm.com)

Innovatech Rocky Mountains  
Wyoming, USA  
[Email: ggoodenow@innovatechrm.com](mailto:ggoodenow@innovatechrm.com)  
[Website: www.innovatechrm.com](http://www.innovatechrm.com)

HLC Ltd  
Northern Illinois, USA  
[Email: djohnson@hlcltd.com](mailto:djohnson@hlcltd.com)  
[Website: www.hlcltd.com](http://www.hlcltd.com)

HLC Ltd  
Southeast Wisconsin, USA  
[Email: djohnson@hlcltd.com](mailto:djohnson@hlcltd.com)  
[Website: www.hlcltd.com](http://www.hlcltd.com)

Fusion Sourcing Group  
New York, USA  
[Email: TDKsales@fusionsourcing.com](mailto:TDKsales@fusionsourcing.com)  
[Website: www.fusionsourcing.com](http://www.fusionsourcing.com)

Fusion Sourcing Group  
Northern New Jersey, USA  
[Email: TDKsales@fusionsourcing.com](mailto:TDKsales@fusionsourcing.com)  
[Website: www.fusionsourcing.com](http://www.fusionsourcing.com)

Enco Marketing  
Michigan, USA  
[Email: Brett.kauffman@encomarketing.com](mailto:Brett.kauffman@encomarketing.com)  
[Website: www.encomarketing.com](http://www.encomarketing.com)

Electro Reps Inc  
Kentucky, USA  
[Email: eri@electro-reps.com](mailto:eri@electro-reps.com)  
[Website: www.electro-reps.com](http://www.electro-reps.com)

Electro Reps Inc  
Ohio, USA  
[Email: eri@electro-reps.com](mailto:eri@electro-reps.com)  
[Website: www.electro-reps.com](http://www.electro-reps.com)

Electro Reps Inc  
Indiana, USA  
[Email: eri@electro-reps.com](mailto:eri@electro-reps.com)  
[Website: www.electro-reps.com](http://www.electro-reps.com)

Electro Reps Inc  
Western Pennsylvania, USA  
[Email: eri@electro-reps.com](mailto:eri@electro-reps.com)  
[Website: www.electro-reps.com](http://www.electro-reps.com)

Earl & Brown Co., Inc.  
Washington, USA  
[Email: dpoulos@earlbrownrep.com](mailto:dpoulos@earlbrownrep.com)  
[Website: www.earlbrownrep.com](http://www.earlbrownrep.com)

Earl & Brown Co., Inc.  
Idaho, USA  
[Email: dpoulos@earlbrownrep.com](mailto:dpoulos@earlbrownrep.com)  
[Website: www.earlbrownrep.com](http://www.earlbrownrep.com)

Earl & Brown Co., Inc.  
Oregon, USA  
[Email: jchinn@earlbrownrep.com](mailto:jchinn@earlbrownrep.com)  
[Website: www.earlbrownrep.com](http://www.earlbrownrep.com)





**TDK Corporation of America**

475 Half Day Road  
Lincolnshire, IL 60069-2934

Web: <http://www.tdk.com>

Reps: <http://www.tdk.com/rep.php>

Sales: <http://www.tdk.com/sales.php>

Distributors: <http://www.tdk.com/distributor.php>