

## Two Pole Heavy Duty PCB / QC Power Relay

# HG4236



### FEATURES

- Two poles heavy duty power relay
- Up to 30A switching capacity
- DC and AC coil available
- 8 mm creepage distance and 4 KV dielectric
- PCB and QC termination

### TYPICAL APPLICATIONS

- Industrial control
- Commercial applications

### CONTACT RATING

Form	2 Form A (2H), 2 Form C (2Z)	
	NO	NC
Resistive	30A, 120VAC / 277VAC	3A, 28VDC / 277VAC
	20A, 28VDC	2A, 480VAC 1A, 600VAC
Motor	1HP, 120VAC 2.5HP, 250VAC	
TV	TV10	
Max. Switching Current	30A	
Max. Switching Voltage	277VAC	

### CONTACT DATA

Material	AgCdO	
Initial Resistance	50 mΩ, max. at 1A, 6VDC	
Service	Mechanical	5 x 10 <sup>6</sup> ops.
	Electrical	10 <sup>5</sup> ops. at 30A, 250VAC or 2HP, 250VAC

### COIL DATA

Type	Coil Voltage Code	Nominal Voltage (VDC/VAC)	Resistance (Ω) ±10%		Must Operate Voltage max. (VDC/VAC)	Must Release Voltage min. (VDC/VAC)
DC	006	6	22		4.5	0.6
	012	12	86		9.0	1.2
	024	24	350		18.0	2.4
	048	48	1390		36.0	4.8
	110	110	7255		82.5	11.0
AC Frequency			50Hz	60Hz		
AC	024A	24	52	39	19.2	4.8
	120A	120	1390	950	96.0	24.0
	208A	208	3800	2841	166.4	41.6
	240A	240	5200	3800	192.0	48.0
	277A	277	7255	5200	221.6	55.4


### CHARACTERISTICS

Operate Time	15 ms.
Release Time	10 ms.
Insulation Resistance	1000 MΩ, at 500 VDC, 50%RH
Dielectric Strength	1500 Vrms, 1 min. between open contacts 4000 Vrms, 1 min. between coil and contacts 2000 Vrms, 1 min. between poles
Shock Resistance	10 g, 11ms, functional; 100 g, destructive
Vibration Resistance	DA 1.65mm, 10 - 55 Hz
Power Consumption	DC Coil: 1.7 W; AC Coil: 4VA; approx.
Ambient Temperature	DC Coil: -55 to 85 C; AC Coil: -40 to 65 C operating
Weight	86 g, approx.

### ORDERING DESIGNATION

Example:	HG4236 /	120	A -	2Z	1	1	C	F
Model								
Coil Voltage Code								
DC/AC								
Nil: DC A: AC								
Contact Form								
2H: 2 Form A; 2Z: 2 Form C								
Mounting Version								
0: PCB; 1: Panel Mount								
Version								
1: Sealed; 2: Dust Cover								
Contact Material								
C: AgCdO								
Thermal Class								
F: UL Class F								

OVERALL DIMENSIONS, MOUNTING HOLES AND WIRING DIAGRAM (mm)



NOTES

- 1. All parameters, unless otherwise specified, are measured at ambient temperature 23°C.
- 2. Custom-made services available with operational quantity. Please let us know your special requirements.
- 3. Specifications subject to change without prior notice.