

NOTES:

1 A COMBINATION OF STEP 1 AND STEP 2 EQUALS THE CONNECTOR SIZE USED IN STEP 7.
EXAMPLE: 208, 330

| REV | DESCRIPTION | BY DATE | APPD |
|-----|----------------------|--------------------|------|
| A | RELEASED PER ECR7264 | C.M.B. 04/05/02 | LMD |

POWER CONNECTOR SYSTEM CODE ORDER CHART



PER ASME Y14.5M-1994
UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES OR INCHES/MM

TOLERANCES:
DECIMALS .XX ± N/A
.XXX ± N/A

ANGLES ±N/A SCALE: N/A

CUSTOMER DRAWING

| | | | |
|-------|----------|----------|---------|
| DRAWN | DATE | APPROVED | DATE |
| BAS | 03/20/00 | LMD | 04/5/02 |

NORTHROP GRUMMAN

Winchester Electronics
400 Park Road
Waterbury, CT 06796

TITLE
POWER CONNECTOR CODE ORDER CHART

| | | | | | |
|------|---|-------|-------------|------|---|
| REV. | A | 26450 | SHT. 1 OF 1 | REV. | A |
|------|---|-------|-------------|------|---|