



SMA Female Connector Solder Attachment 4 Hole Flange Solder Cup Terminal, .500 inch Hole Spacing

TECHNICAL DATA SHEET

PE4527

SMA Female Connector Solder Attachment 4 Hole Flange Solder Cup Terminal, .500 inch Hole Spacing

Configuration

Connector SMA Female
Connector Specification MIL-STD-348
Connector Interface Type Solder Cup
Cable Attachment Method (Shield/Contact) Solder
Body Style Straight
Mount Method 4 Hole Flange

Electrical Specifications

Impedance, Ohms 50

Mechanical Specifications

Size

 Length, in [mm]
 0.578 [14.68]

 Width/Dia., in [mm]
 0.687 [17.45]

 Height, in [mm]
 0.687 [17.45]

 Weight, lbs [g]
 0.013 [5.9]

Connector

Type SMA Female
Contact Material and Plating Beryllium Copper, Gold
Contact Plating Specification MIL-G-45204, Type II
Body Material and Plating Stainless Steel, Gold
Body Plating Specification MIL-G-45204, Type II
Dielectric Type Teflon

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female Connector Solder Attachment 4 Hole Flange Solder Cup Terminal, .500 inch Hole Spacing PE4527

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.







SMA Female Connector Solder Attachment 4 Hole Flange Solder Cup Terminal, .500 inch Hole Spacing

TECHNICAL DATA SHEET

PE4527

SMA Female Connector Solder Attachment 4 Hole Flange Solder Cup Terminal, .500 inch Hole Spacing from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female Connector Solder Attachment 4 Hole Flange Solder Cup Terminal, .500 inch Hole Spacing PE4527


URL: http://www.pasternack.com/sma-female-standard-solder-cup-terminal-connector-pe4527-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



M	MATERIALS
ВОДУ	STAINLESS STEEL GOLD PLATED
CONTACT	GOLD PLATED
INSULATOR	PTFE





MOUNTING HOLES



PASTERNACK ENTERPRISES, INC.

P.O BOX 16759, IRVINE, CA 92623 PHONE (949) 261-1920 FAX (949) 261-7451

WEB ADDRESS: www.pasternack.com E-MAIL ADDRESS: sales@pasternack.com COAXIAL & FIBER OPTICS

ER CUP

SMA FEMALE, PANEL MOUNT, SOLDE TERMINAL
SMA FEMALE, TERMINAL

MOUNT, SOLDE	
; PANEL M	
SMA FEMALE, PANEL I TERMINAL	
DES.	

PE4527

DWG TITLE

127

SCALE N/A

CAD FILE 052202

CAD FILE	
:M NO. 53919	
E A FSCM	C L H
SIZE	

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.