



Shorting Dust Cap for SMA Male

TECHNICAL DATA SHEET

PE6006

Shorting Dust Cap for SMA Male

Configuration

Connector SMA Male Shorting
Connector Specification MIL-STD-348A
Chain Option No Chain

Mechanical Specifications

Temperature

Operating Range, deg C -65 to +165

Size

Length, in [mm] 0.335 [8.51] Width, in [mm] 0.315 [8]

Connector

Type SMA Male Shorting Contact Material and Plating Brass, Gold Contact Plating Specification 30µ in. minimum Coupling Nut Material and Plating Brass, Nickel Coupling Nut Plating Specification 100µ in. minimum Hex Size, in. 5/16 Torque, in-lbs [Nm] 5 [0.57] Body Material and Plating Brass, Gold **Body Plating Specification** 30µ in. minimum

Dielectric Type Teflon

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

Shorting Dust Cap for SMA Male from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Shorting Dust Cap for SMA Male PE6006

URL: http://www.pasternack.com/50-ohm-sma-male-short-cap-pe6006-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE6006 CAD Drawing Shorting Dust Cap for SMA Male

