



SPECIFICATIONS

FREQUENCY RANGE: 2 GHz - 4 GHz
 VSWR: 1.6:1, MAXIMUM
 INSERTION LOSS: 1.2 dB, MAXIMUM
 ISOLATION: 75 dB, MINIMUM
 SWITCHING SPEED: 100 nsec, MAXIMUM
 POWER WATTS: 1.0, MAXIMUM
 DC BIAS: +5.0 ±0.5V @ 100mA, MAXIMUM
 -15.0 ±3.0V @ 100mA, MAXIMUM

CONTROLS:

TTL LOGIC 0: J1-J2, J3-J4 LOW LOSS
 J1-J4, J2-J3 ISOLATION
 TTL LOGIC 1: J1-J4, J2-J3 LOW LOSS
 J1-J2, J3-J4 ISOLATION



PASTERNAK ENTERPRISES, INC.

P.O. BOX 16759, IRVINE, CA 92623
 PHONE (949) 261-1920 FAX (949) 261-7451

WEB ADDRESS: www.pasternack.com
 E-MAIL ADDRESS: sales@pasternack.com

COAXIAL & FIBER OPTICS

DWG TITLE

PE7135

DES. SMA FEMALE, TRANSFER SWITCH
 FREQUENCY RANGE: 2 GHz TO 4 GHz

REV. A **FSCM NO. 53919**

CAD FILE 030309

SCALE N/A

SIZE A 147

NOTES:

1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES.