Features

Regulated Converters

- UL-60950-1 / CSA C22.2 certified
- 3W DIP Package
- 4kVDC & 6kVDC Isolation
- Regulated Output
- Continuous Short Circuit Protection Auto-Restarting
- Wide Input 2:1 & 4:1
- UL94V-0 Package Material
- Cost Effective
- 100% Burned In
- Efficiency to 86%

Selection Guide

Part Number DIP24 (SMD)	Input Voltage (VDC)	Output Voltage (VDC)	Max. Cap. Load (µF)	Output Current (mA)	Efficiency (%)
REC3-xx3.3SRW (H4/H6)	4.5 - 9, 9 - 18, 18 - 36, 36 - 72	3.3	2200	900	66-76
REC3-xx05SRW (H4/H6)	4.5 - 9, 9 - 18, 18 - 36, 36 - 72	5	1000	600	71-79
REC3-xx09SRW (H4/H6)	4.5 - 9, 9 - 18, 18 - 36, 36 - 72	9	470	330	74-83
REC3-xx12SRW (H4/H6)	4.5 - 9, 9 - 18, 18 - 36, 36 - 72	12	220	250	75-85
REC3-xx15SRW (H4/H6)	4.5 - 9, 9 - 18, 18 - 36, 36 - 72	15	120	200	75-86
REC3-xx05DRW (H4/H6)	4.5 - 9, 9 - 18, 18 - 36, 36 - 72	±5	±470	±300	74-83
REC3-xx09DRW (H4/H6)	4.5 - 9, 9 - 18, 18 - 36, 36 - 72	±9	±220	±165	81-84
REC3-xx12DRW (H4/H6)	4.5 - 9, 9 - 18, 18 - 36, 36 - 72	±12	±100	±125	75-85
REC3-xx15DRW (H4/H6)	4.5 - 9, 9 - 18, 18 - 36, 36 - 72	±15	±68	±100	75-86
REC3-xx3.3SRWZ (H4/H6)	9 - 36, 18 - 72	3.3	2200	900	77-79
REC3-xx05SRWZ (H4/H6)	9 - 36, 18 - 72	5	1000	600	78-80
REC3-xx09SRWZ (H4/H6)	9 - 36, 18 - 72	9	470	330	80-83
REC3-xx12SRWZ (H4/H6)	9 - 36, 18 - 72	12	220	250	83-85
REC3-xx15SRWZ (H4/H6)	9 - 36, 18 - 72	15	120	200	83-85
REC3-xx05DRWZ (H4/H6)	9 - 36, 18 - 72	±5	±470	±300	77-80
REC3-xx09DRWZ (H4/H6)	9 - 36, 18 - 72	±9	±220	±165	81-84
REC3-xx12DRWZ (H4/H6)	9 - 36, 18 - 72	±12	±100	±125	83-85
REC3-xx15DRWZ (H4/H6)	9 - 36, 18 - 72	±15	±68	±100	83-85

2:1 Input
(REC3-S/DRWH4/H6)
xx = 4.5-9Vin = 05
xx = 9-18Vin = 12
xx = 18-36Vin = 24
xx = 36-72Vin = 48

4:1 Input
(REC3-S/DRWZ(H4/H6))
xx = 9-36Vin = 24
xx = 18-72Vin = 48

* add suffix /**H4** for 4kVDC isolation or /**H6** for 6kVDC isolation
* add suffix "/**A**" or "/**C**" for Pinning, see next page
"**B**" Pinning is NOT available for this series !
* add suffix "/**M**" for metal case
* add suffix "/**SMD**" for SMD package
e.g. REC3-2412SRW/H4/AM =
4kVDC isol. / Pinout "**A**" / metal case

Description

This series offers high isolation of 4kVDC (= option "H4") or 6kVDC (= option "H6") making it ideal for medical applications and other sophisticated industrial applications. Packaging can be either DIP-24 non-conductive plastic or 5-side-shielded DIP24 metal case (= option "M") as well as DIP24-SMD case (= option "SMD"). For all the above variants, 2 industry-standard pinouts (= option "A" or "C") are available.

Specifications (Core Operating Area)

Input Voltage Range	2:1 & 4:1
Output Voltage Accuracy	±2% max.
Line Regulation (HL-LL)	±0.4% max.

continued on next page

ECONOLINE
DC/DC-Converter

REC3-S_DRW(Z)/H4,H6 Series

3 Watt DIP24 & SMD Single & Dual Output



EN-60950-1 Certified
UL-60950-1 Certified
EN-60601-1 Certified

RECOM

Notes :

1. If the options "/**M**" for metal case and "/**SMD**" for SMD pinout are combined, the maximum allowed isolation voltage is 2kVDC because of the shorter distances between pins and the metal case, so only available SMD-option in metal-case is "/**H2**".
DIP-24 through-hole case and SMD-plastic case are not affected and offer the full isolation barriers of 4kVDC for "/**H4**" option and 6kVDC for "/**H6**".

REC3-S_DRW(Z) /H4,H6 Series

Specifications (Core Operating Area)

Load Regulation (for output load current change from 20% to 100%)			±0.6% max.
Output Ripple and Noise (0,1µF capacitor on output, 20MHz BW)			50mVp-p max.
Switching Frequency at Full Load and nominal Input Voltage		2:1 Input types 4:1 Input types	90kHz min. / 150kHz max. 120kHz min. / 180kHz max.
Input Filter			Pi Network
Efficiency at Full Load			see above
No Load Power Consumption			300mW max.
Isolation Voltage Rated Working Voltage	H4 types (see note)	(tested for 1 second) (long term isolation)	4000VDC min. see Application Notes
Isolation Voltage Rated Working Voltage	H6 types (see note)	(tested for 1 second) (long term isolation)	6000VDC min. see Application Notes
Isolation Capacitance		2:1 Input types 4:1 Input types	20pF min. / 60pF max. 40pF min. / 80pF max.
Isolation Resistance			1 GΩ min.
Short Circuit Protection			Continuous, Auto Restart
Operating Temperature Range (free air convection)		5V input types others	-40°C to +80°C (see Graph) -40°C to +85°C (see Graph)
Storage Temperature Range			-55°C to +125°C
Relative Humidity			95% RH
Case Material			Non-Conductive Plastic
Thermal Impedance		Natural convection	20°C/W for metal case
Package Weight			13g
MTBF (+25°C) } *Detailed Information see Application Notes chapter "MTBF"*		using MIL-HDBK 217F	1043 x 10^3 hours
(+85°C) }		using MIL-HDBK 217F	186 x 10^3 hours

Derating-Graph (Ambient Temperature)





Typical Characteristics

Single 2:1 Input



Single 2:1 Input



Dual 2:1 Input



Single 4:1 Input



Single 4:1 Input



Dual 4:1 Input



REC3-S_DRW(Z) /H4,H6Series

Package Style and Pinning (mm) DIP 24 , Wide Input 2:1 & 4:1

Package A





3rd angle projection



Recommended Footprint Details



Pin Connections		
Pin #	Single	Dual
2	–Vin	–Vin
3	–Vin	–Vin
9	NC	Com
11	NC	–Vout
14	+Vout	+Vout
16	–Vout	Com
22	+Vin	+Vin
23	+Vin	+Vin

NC = No Connection
XX.X ± 0.5 mm
XX.XX ± 0.25 mm

Package C







Recommended Footprint Details



Pin Connections		
Pin #	Single	Dual
1	+Vin	+Vin
2	+Vin	+Vin
10	NC	Com
11	NC	Com
12	–Vout	NC
13	+Vout	–Vout
15	NC	+Vout
23	–Vin	–Vin
24	–Vin	–Vin

NC = No Connection
XX.X ± 0.5 mm
XX.XX ± 0.25 mm

Mechanical drawings of DIP24 SMD case





Recommended Footprint Details





All unused pins are NC (No Connection). SMD pin connections follow standard package pinning.

Tol.: ± 0.35 mm

for all packages incl.SMD case the length of plastic case is 31,8mm, length of metal case 32.0mm