




# SS32H THRU SS310H

## SURFACE MOUNT SCHOTTKY BARRIER RECTIFIER

*Reverse Voltage - 20 to 100 Volts*

*Forward Current - 3.0 Amperes*

**SMB / DO-214AA**



\*Dimensions in inches and (millimeters)



**Lead free product**

### FEATURES

- \* Halogen-free type
- \* Compliance to RoHS product
- \* Plastic package has Underwriters Laboratory Flammability Classifications 94V-0
- \* For surface mount applications
- \* Low power loss, high efficiency
- \* High current capability, low forward voltage drop
- Guardring for overvoltage protection
- \* For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications
- \* High temperature soldering guaranteed : 260°C/10 seconds, at terminals

### MECHANICAL DATA

**Case :** JEDEC DO-214AA molded plastic body  
**Terminals :** Tin plated, solderable per MIL-STD-750D Method 2026  
**Polarity :** Color band denotes cathode end  
**Weight :** 0.003 ounces , 0.093 gram

## MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25 °C ambient temperature unless otherwise specified.		SYMBOLS	SS32H	SS34H	SS36H	SS310H	UNITS
Maximum repetitive peak reverse voltage		VRRM	20	40	60	100	Volts
Maximum RMS voltage		VRMS	14	28	42	70	Volts
Maximum DC blocking voltage		VDC	20	40	60	100	Volts
Maximum average forward rectified current (SEE FIG.1)		I(AV)	3.0				Amps
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)		IFSM	80				Amps
Maximum instantaneous forward voltage at 3.0 A (NOTE 1)		VF	0.50		0.70	0.85	Volts
Maximum DC reverse current at rated DC blocking voltage (NOTE 1)	TA=25°C	IR	0.5				mA
	TA=100°C		20		10		
Typical thermal resistance (NOTE 2)		R θJA R θJL	55 17				°C / W
Operating junction temperature range		TJ	-55 to +125		-55 to +150		°C
Storage temperature range		TSTG	-55 to +150				°C

NOTES : (1) Pulse test : 300us pulse width, 1% duty cycle  
 (2) P.C.B. mounted with 0.55 x 0.55" ( 14 x 14mm ) copper pad areas

# RATINGS AND CHARACTERISTIC CURVES SS32H THRU SS310H

FIG. 1 - FORWARD CURRENT DERATING CURVE




FIG. 2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG. 3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 4 - TYPICAL REVERSE CURRENT CHARACTERISTICS




FIG. 5 - TYPICAL JUNCTION CAPACITANCE

