


LOW VOLTAGE RECTIFIER Transformer  
with horizontal channel frames.

- Primary voltage, 115 Volts, 60 Hz.
- Primary and secondary leads 8-10" long.
- 2-hole horizontal mounting.
- 5 sizes are available, covering the range: 10 to 50 VA.
- CSA listed (LR 47366).



## MECHANICAL



Dimensions, Inches

| P/N  | DIMENSIONS |      |      | PIN SPACING<br>A |
|------|------------|------|------|------------------|
|      | L          | W    | H    |                  |
| 4766 | 3.25       | 2.00 | 2.00 | 2.81             |
| 4767 | 3.25       | 2.25 | 2.00 | 2.81             |
| 4768 | 3.69       | 2.13 | 2.31 | 3.13             |
| 4769 | 4.00       | 2.25 | 2.63 | 3.56             |
| 4770 | 4.00       | 2.50 | 2.63 | 3.56             |

## ELECTRICAL SPECIFICATION

| Part No. | Secondary Voltages (A-A) |            |              | Part No. | Secondary Voltages (A-A) |            |              |
|----------|--------------------------|------------|--------------|----------|--------------------------|------------|--------------|
|          | F.L. Volts               | N.L. Volts | Current Amps |          | F.L. Volts               | N.L. Volts | Current Amps |
| 4766-01  | 6.3                      | 7.25       | 1.20         | 4769-01  | 14.0                     | 15.30      | 2.00         |
| 4766-02  | 6.3                      | 7.14       | 2.00         | 4769-02  | 18.0                     | 19.60      | 1.50         |
| 4766-03  | 10.0                     | 11.00      | 1.00         |          |                          |            |              |
| 4766-04  | 14.0                     | 16.00      | 1.00         | 4770-01  | 8.5                      | 9.04       | 4.00         |
| 4766-05  | 20.0                     | 22.00      | 0.50         | 4770-02  | 10.0                     | 10.50      | 3.00         |
| 4766-06  | 28.0                     | 32.00      | 0.50         | 4770-03  | 16.0                     | 17.00      | 2.20         |
| 4766-07  | 30.0                     | 34.20      | 0.50         | 4770-04  | 16.0                     | 17.40      | 3.00         |
| 4766-08  | 36.0                     | 39.40      | 0.30         | 4770-05  | 20.0                     | 21.40      | 2.00         |
| 4766-09  | 44.0                     | 50.60      | 0.25         | 4770-06  | 25.0                     | 26.80      | 1.50         |
| 4766-10  | 50.0                     | 57.00      | 0.30         | 4770-07  | 33.0                     | 35.00      | 1.00         |
|          |                          |            |              | 4770-08  | 36.0                     | 39.50      | 1.00         |
| 4767-01  | 8.5                      | 9.60       | 2.00         | 4770-09  | 44.0                     | 47.40      | 1.00         |
| 4767-02  | 36.0                     | 40.00      | 0.50         | 4770-10  | 50.0                     | 54.50      | 1.00         |
| 4767-03  | 16.0                     | 17.60      | 1.00         | 4770-11  | 60.0                     | 65.20      | 0.50         |
|          |                          |            |              | 4770-12  | 80.0                     | 85.50      | 0.50         |
| 4768-01  | 6.3                      | 6.90       | 4.00         | 4770-13  | 100.0                    | 107.00     | 0.50         |
| 4768-02  | 8.5                      | 9.50       | 3.00         | 4770-14  | 120.0                    | 129.50     | 0.30         |
| 4768-03  | 10.0                     | 10.80      | 2.00         |          |                          |            |              |
| 4768-04  | 12.6                     | 13.80      | 2.00         |          |                          |            |              |
| 4768-05  | 20.0                     | 22.00      | 1.00         |          |                          |            |              |
| 4768-06  | 25.0                     | 27.50      | 1.00         |          |                          |            |              |
| 4768-07  | 28.0                     | 30.80      | 1.00         |          |                          |            |              |
| 4768-08  | 44.0                     | 48.10      | 0.50         |          |                          |            |              |
| 4768-09  | 50.0                     | 55.00      | 0.50         |          |                          |            |              |