


# Power Transformers Fully Enclosed 4808 - 4820





LOW VOLTAGE RECTIFIER Transformers with fully enclosed vertical end covers.

- Primary voltage, 115 Volts, 60 Hz.
- Primary and secondary leads 8-10" long.
- 4-hole vertical mounting.
- 13 sizes are available, covering the range: 100 to 500 VA.
- CSA listed (LR 47366).



## MECHANICAL



Dimensions, Inches

| P/N  | DIMENSIONS |      |      | D    | E    | F     | G     |
|------|------------|------|------|------|------|-------|-------|
|      | L          | W    | H    |      |      |       |       |
| 4808 | 3.13       | 3.63 | 3.81 | 2.50 | 2.44 | 0.390 | 0.203 |
| 4809 | 3.13       | 3.88 | 3.81 | 2.50 | 2.69 | 0.390 | 0.203 |
| 4810 | 3.13       | 4.13 | 3.81 | 2.50 | 2.94 | 0.390 | 0.203 |
| 4811 | 3.13       | 4.38 | 3.81 | 2.50 | 3.19 | 0.390 | 0.203 |
| 4812 | 3.13       | 4.63 | 3.81 | 2.50 | 3.44 | 0.390 | 0.203 |
| 4813 | 3.75       | 4.50 | 4.56 | 3.00 | 3.44 | 0.375 | 0.187 |
| 4814 | 3.75       | 4.75 | 4.56 | 3.00 | 3.69 | 0.375 | 0.187 |
| 4815 | 3.75       | 5.00 | 4.56 | 3.00 | 3.94 | 0.375 | 0.187 |
| 4816 | 3.75       | 5.25 | 4.56 | 3.00 | 4.19 | 0.375 | 0.187 |
| 4817 | 3.75       | 5.50 | 4.56 | 3.00 | 4.44 | 0.375 | 0.187 |
| 4818 | 3.75       | 5.75 | 4.56 | 3.00 | 4.69 | 0.375 | 0.187 |
| 4819 | 3.75       | 6.00 | 4.56 | 3.00 | 4.94 | 0.375 | 0.187 |
| 4820 | 3.75       | 6.25 | 4.56 | 3.00 | 5.19 | 0.375 | 0.187 |

## ELECTRICAL SPECIFICATION

| Part No. | Secondary Voltages (A-A) |            |              |
|----------|--------------------------|------------|--------------|
|          | F.L. Volts               | N.L. Volts | Current Amps |
| 4808-01  | 6.3                      | 6.75       | 16.00        |
| 4808-02  | 7.5                      | 8.10       | 15.00        |
| 4808-03  | 11.0                     | 11.80      | 10.00        |
| 4808-04  | 20.0                     | 21.00      | 5.00         |
| 4808-05  | 36.0                     | 37.90      | 3.00         |
| 4808-06  | 55.0                     | 58.50      | 2.00         |
| 4808-07  | 60.0                     | 64.00      | 2.00         |
| 4809-01  | 12.6                     | 13.20      | 10.00        |
| 4809-02  | 25.0                     | 27.20      | 5.00         |
| 4810-01  | 30.0                     | 31.40      | 5.00         |
| 4811-01  | 5.0                      | 5.30       | 30.00        |
| 4811-02  | 7.5                      | 8.00       | 21.00        |
| 4811-03  | 11.0                     | 11.70      | 15.00        |
| 4811-04  | 18.0                     | 18.80      | 10.00        |
| 4811-05  | 36.0                     | 38.20      | 5.00         |
| 4811-06  | 70.0                     | 73.00      | 2.00         |
| 4811-07  | 80.0                     | 82.70      | 2.00         |
| 4812-01  | 60.0                     | 62.20      | 3.00         |
| 4813-01  | 50.0                     | 51.80      | 5.00         |

| Part No. | Secondary Voltages (A-A) |            |              |
|----------|--------------------------|------------|--------------|
|          | F.L. Volts               | N.L. Volts | Current Amps |
| 4814-01  | 12.6                     | 13.00      | 20.00        |
| 4814-02  | 18.0                     | 18.80      | 15.00        |
| 4814-03  | 22.0                     | 22.30      | 12.00        |
| 4814-04  | 25.0                     | 26.10      | 10.00        |
| 4814-05  | 30.0                     | 31.40      | 10.00        |
| 4814-06  | 50.0                     | 51.80      | 5.00         |
| 4814-07  | 200.0                    | 212.00     | 0.87         |
| 4815-01  | 36.0                     | 37.40      | 8.00         |
| 4815-02  | 70.0                     | 72.00      | 4.00         |
| 4816-01  | 60.0                     | 62.00      | 5.00         |
| 4816-02  | 80.0                     | 82.50      | 4.00         |
| 4817-01  | 20.0                     | 21.40      | 16.00        |
| 4818-01  | 18.0                     | 18.50      | 20.00        |
| 4819-01  | 36.0                     | 38.00      | 12.00        |
| 4820-01  | 22.0                     | 22.50      | 20.00        |
| 4820-02  | 100.0                    | 103.70     | 5.00         |

ISSUE: C 4808.CHP 950712